



2/3" F1.4/16 C Mount

				Working distance	Optical Magnification	2/3" Field of View(mm)	
Focal Length		f=16mm		mm		H	V
Max Diameter (Ratio)		F=1:1.4~16		900	0.018X	503.2	376.8
Picture Size		2/3"(8.8x6.6mm)	1/2"(6.4x4.8mm)	850	0.019X	475.6	356.2
Angle	H	30.3°	22.3°	800	0.020X	448.0	335.5
	V	23°	16.8°	750	0.021X	420.4	314.8
	D	37.3°	27.8°	700	0.023X	392.8	294.1
Object Dimension at 300mm	H	170.4mm	123.7mm	650	0.024X	365.2	273.4
	V	127.6mm	92.7mm	600	0.026X	337.6	252.8
	D	212.8mm	154.9mm	550	0.029X	310.0	232.1
Distortion (TV)		<0.1%	<0.3%	500	0.031X	282.5	211.4
Focus distance(min)		0.1m		450	0.035X	254.9	190.7
Flange back		17.526mm in air		400	0.039X	227.3	170.0
Back focus		12.7mm in air		350	0.044X	199.7	149.4
Filter screw size		M30.5x0.5		300	0.052X	170.4	127.6
Front/Rear Effective Dia		Front $\phi 19$ mm Rear $\phi 14.2$ mm		250	0.061X	144.5	108.0
Mount		C-Mount		200	0.076X	116.9	87.3
Temperature Range		-10~+50°C		150	0.100X	89.3	66.6
Storage Temperature Range		-20~+60°C		100	0.145X	61.7	45.9

				TOLERANCE :		三角法	材料(环保)	单位	比例
				LINEARITY TOLERANCES ± 0.05			---	mm	2:1
				ANGULAR TOLERANCES ARE $\pm 30'$					
				DRAFT ANGLES AREA $\pm 0.5'$ /SIDE					
F		1	---	CHP	2019.03.15	设计	名称	FL-A1602D	页码
		1	---	CHP	2017.09.11	校对			1/1
		2	----	CHP	2016-10-08	审核			版本
	标记	处数	更改文件号	担当	变更日期	批准			代号